

MODEL	Deadrise @ transom [approx]	Weight dry [kg][approx]	Beam	Bottom plate mm	Side plates mm	Self draining deck mm	Transom height	Recommend hp in 4 stroke outboards	Min/Max HP	Hull length Mtr/ft not including bow sprit [approx]	Overall length including bow sprit [approx]	Freeboard from chine to top of gunnel	Freeboard from self draining deck to top of gunnel in mm	Hight from keel add 200mm for hardtops & centre cabs
Excalibur series														
6000	18	940	2600	5	4	3	25	130	130-200	6.0 / 19.73	6.5 / 21.38	1050	780	2750
6200	18	965	2600	5	4	3	25	135	130-225	6.2 / 20.40	6.7 / 22.03	1050	780	2750
6500	18	1000	2600	5	4	3	25	150	130-225	6.5 / 21.38	7.0 / 23.02	1050	780	2750
6800	18	1040	2600	5	4	3	25	150	130-225	6.8 / 22.36	7.3 / 24.01	1050	780	2750
7000	18	1065	2600	5	4	3	25	150	150-225	7.0 / 23.02	7.5 / 24.67	1050	780	2750
7200	18	1100	2600	5	4	3	25	175	150-225	7.2 / 23.68	7.7 / 25.32	1050	780	2750
7500	18	1140	2600	5	4	3	25	175	150-225	7.5 / 24.67	8.0 / 26.31	1050	780	2750
Sailfisher series														
5500	16	685	2500	4	4	3	25	100	75-115	5.5 / 18.09	6.0 / 19.73	900	650	2730
5800	16	780	2500	5	4	3	25	115	90-150	5.8 / 19.07	6.3 / 20.72	900	650	2730
6000	16	835	2500	5	4	3	25	115	100-150	6.0 / 19.73	6.5 / 21.38	900	650	2730
6200	16	895	2500	5	4	3	25	130	130-175	6.2 / 20.40	6.7 / 22.03	900	650	2730
6500	16	935	2500	5	4	3	25	150	130-200	6.5 / 21.38	7.0 / 23.02	900	650	2730
6800	16	975	2500	5	4	3	25	150	140-200	6.8 / 22.36	7.3 / 24.01	900	650	2730
Estuary														
5300	14	630	2300	4	4	3	20	80	75-115	5.3 / 17.43	5.8 / 19.07	850	650	2680
5500	14	685	2300	4	4	3	20	100	80-115	5.5 / 18.09	6.0 / 19.73	850	650	2680
Ultimate														
5300	16	695	2400	5	4	3	25	90	75-115	5.3 / 17.43	5.8 / 19.07	930	650	2760
5500	16	710	2400	5	4	3	25	90	80-115	5.5 / 18.09	6.0 / 19.73	930	650	2760
5800	16	750	2400	5	4	3	25	115	100-150	5.8 / 19.07	6.3 / 20.72	930	700	2760
Barrakuda														
4800	14	500	2300	4	4	3	20	60	50-80	4.8 / 15.78	5.3 / 17.43	850	650	1450
5000	14	525	2300	4	4	3	20	60	50-90	5.0 / 16.44	5.5 / 18.09	850	650	1450
5300	14	555	2300	4	4	3	20	75	75-115	5.3 / 17.43	5.8 / 19.07	850	650	1450
5500	14	570	2300	4	4	3	20	90	80-115	5.5 / 18.09	6.0 / 19.73	850	650	1450
5800	16	600	2500	5	4	3	25	115	100-150	5.8 / 19.07	6.3 / 20.72	850	650	1550
Centre console														
4800	14	500	2300	4	4	3	20	60	50-80	4.8 / 15.78	5.3 / 17.43	850	600	1450
5000	14	525	2300	4	4	3	20	60	50-90	5.0 / 16.44	5.5 / 18.09	850	600	1450
5300	14	555	2300	4	4	3	20	75	75-115	5.3 / 17.43	5.8 / 19.07	850	600	1450
5500	14	570	2300	4	4	3	20	90	80-115	5.5 / 18.09	6.0 / 19.73	850	600	1450
5800	16	600	2500	5	4	3	25	115	100-150	5.8 / 19.07	6.3 / 20.72	900	650	1450
6000	16	835	2500	5	4	3	25	115	100-150	6.0 / 19.73	6.5 / 21.38	900	650	1550
6200	16	895	2500	5	4	3	25	130	130-175	6.2 / 20.40	6.7 / 22.03	900	650	1550
6500	16	935	2500	5	4	3	25	150	130-200	6.5 / 21.38	7.0 / 23.02	900	650	1550
Runabouts														
4800	14	500	2300	4	4	3	20	60	50-80	4.8 / 15.78	5.3 / 17.43	800	600	1760
5000	14	525	2300	4	4	3	20	60	50-90	5.0 / 16.44	5.5 / 18.09	800	600	1760
5300	14	555	2300	4	4	3	20	75	75-115	5.3 / 17.43	5.8 / 19.07	800	600	1760
5500	14	570	2300	4	4	3	20	90	80-115	5.5 / 18.09	6.0 / 19.73	800	600	1760
5800	14	600	2300	5	4	3	25	115	100-150	5.8 / 19.07	6.3 / 20.72	900	650	1860

Extrem open													
4500	14	475	2100	4	4	3	20	50	40-60	4.5 / 14.80	5.0 / 16.44		
4800	14	500	2300	4	4	3	20	60	50-80	4.8 / 15.78	5.3 / 17.43		
5000	14	525	2300	4	4	3	20	60	50-90	5.0 / 16.44	5.5 / 18.09		
5300	14	555	2300	4	4	3	20	80	60-100	5.3 / 17.43	5.8 / 19.07		
5500	14	570	2300	4	4	3	20	80	75-115	5.5 / 18.09	6.0 / 19.73		